



CM EX9000 ROADLINE PAINT (NON-REFLECTIVE)

Product Code : CM RLP-9102/9103/9104/9105

Product Descriptions

CM EX9000 Non-Reflective Roadline Paint is an alkyd/chlorinated rubber based paint for road markings such as car parking lines, centerlines, edge lines, crosswalks etc. It is a fast drying roadline marking paint, has excellent resistance to bitumen bleed through and excellent abrasion resistance.

Recommended Uses

Ideals for road markings like car parking lines, centerlines, edge lines, crosswalks etc.

Product Characteristics

Composition:

Pigment	Titanium Dioxide and Mineral extenders
Binder	Solution Acrylic resin
Solvent	
Volume Solid	60% (approximately)

Properties :

Colour Range	White Ref:9102 Black Ref:9103 Yellow Ref:9104 Red Ref:9105
Texture	Matt
Shelf life/Storage	Use within 12 months of delivery.Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner.
Standard Packing Size	5 Litres

Typical Performance Data (approx.):

Coverage	Approximately 9m ² per litre *Actual coverage is dependent on substrate condition. *These figures do not include wastage.
Recommended no. of coats	1-2 coats for new surface
Drying time (Application Temperature 25'c to 30'c)	Touch Dry: 5-10 minutes Hard Dry : 20-30 minutes
Recoating Interval	8 Hours

Directions for use

Preparation:

All surfaces must be clean, dry, free from grease and free from all defective or poorly adhering material, etc. Lack of adequate surface preparation is usually the cause of flaking and poor adhesion.

New Laid Concrete

1. Must be fully cured and dry.
2. Surface must be clean and free of any contamination, laitance or friable material.
3. All loose dirt and aggressive must be brushed away and surface must be dry during painting.

Bitumen/Asphalt

1. Surfaces must be clean, dry and free of any contamination.

*Newly laid bitumen based surface (up to six month) will need to be sealed with a coat of emulsion paint in order to prevent bleeding.

*Due to the wide variety of Bitumen/Asphalt available. It is recommended to apply a small test area to test the compatibility of the CM EX9000 Roadline paint prior to use.

Application:

- 1) Brush/Roller : Supplied ready to use.

Health, Safety and Environmental information:

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place. Containers that are opened should be properly released and keep upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.