



CM EX9000 SELF ETCHING PRIMER

Product Code : CM EX9 SEP200/SEP300

Product Descriptions

CM EX9000 Self Etching Primer is a 100% Acrylic air drying solvent based formulated primer which chemically protects against the corrosion process. No additional hardener is required. Recommended for protecting bare metal, galvanized steel and aluminium. It is designed to give maximum adhesion and corrosion resistance on all type of bare metal, galvanized steel and aluminium.

Recommended Uses

Highly recommended as an excellent performance primer prior to painting metal material surfaces (bare metal, galvanized steel and aluminium).

Product Characteristics

Composition:

Pigment	Lightfast Non-Lead Pigments
Binder	100% Pure Acrylic
Solvent	Toluene
Volume Solid	30%

Properties :

Colour Range	Light Grey ref: CM EX9 SEP300 Grey Black ref: CM EX9 SEP200
Texture	Matt
Shelf life/Storage	Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner.
Standard Packing Size	1Litre & 5litres *Other Sizes by special arrangement.

Typical Performance Data (approx.):

Coverage	Approximately 10-15m ² per litre *Actual coverage is dependent on substrate condition. *These figures do not include wastage.
Recommended no. of coats	1-2 coats
Drying time (Application Temperature 25'c to 30'c)	Touch Dry: ≥ 1 Hours Hard Dry : ≥ 4 Hours
Recoating Interval	≥ 8 hours

Directions for use

Preparation:

All surfaces must be clean, dry, free from grease and free from all defective or poorly adhering material. Abrade the surfaces with sandpaper if necessary.

Application:

- 1) Brush and Roller: Paint is ready for use after thorough stirring. Thinner with 5% **CM 202 Thinner** by volume if necessary.
- 2) Compressed Air Spray: Dilute 10%-20% **CM 202 Thinner** by volume if necessary.

Recommended Paint System

Metal Surfaces

Sequence	Product Name	No. of Coats
Primer	CM EX9000 Self Etching Primer	1
Undercoat	CM EX9000 Excellent White Undercoat	1
Finish	CM 9900 Premium High Gloss/ CM 5500 Royal High Gloss	2

Health, Safety and Environmental information:

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place.

Containers that are opened should be properly released and kept upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.