



CM FLOOR DRESSING

Product Code : CM FLD

Product Descriptions

CM Floor Dressing is a one pack air drying type of polyurethane Varnish which does not require any addition of hardener. It is specially formulated for parquet floor. It dries rapidly to an extremely durable and flexible clear finish for wood surface that does not hide the wood grains. As it is a one pack polyurethane, it is easy to apply giving a good levelling and high gloss finish.

Recommended Uses

Highly recommended use for parquet floor and wooden surface. With its unique formulation, it has great resistant to most household material like alcohol, sauce, lipstick etc. It also has excellent resistance to hot and cold water.

Product Characteristics

Composition:

Pigment	None
Binder	Alkyd modified polyurethane
Solvent	White Spirit
Volume Solid	45%±

Properties :

Colour Range	Clear
Texture	High Gloss
Shelf life/Storage	Use within 24 months of delivery.Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner.
Standard Packing Size	1 Litre and 5 Litres *Other Sizes by special arrangement.

Typical Performance Data (approx.):

Coverage	Approximately 7-12 m ² per litre *Actual coverage is dependent on substrate condition. *These figures do not include wastage.
Recommended no. of coats	3 coat
Drying time (Application Temperature 25'c to 30'c)	Touch Dry: 30 Minutes Hard Dry : 4 Hours
Recoating Interval	≥ 4 Hours

Directions for use

Preparation:

All surfaces must be clean, dry, free from grease and free from all defective or poorly adhering material. Abrade the surfaces with sandpaper if necessary. Oil and grease should be removed by solvent cleaning.

a) Bare wood

1. Smoothen the surface to be painted using floor sander or sandpaper of Grade 80 or Grade 100.
2. Fill the wood grains with appropriate filler if necessary.
3. Ensure surface is clean, dry and free from wax before applying the first coat. Allow the paint to dry. Dry sand lightly between the 1st and 2nd coat.

a) Painted wood

1. Ensure surface is sound, clean, dry, smooth and free from wax before applying the first coat. Smoothen surface with sandpaper and then clean off and dry. Fill the wood grains with appropriate filler if necessary.
2. If the previous paint film is in sound condition and without wax, smoothen it with sandpaper. Clean off and dry.
3. For old paint which is in sound condition and without wax, smoothen it with sandpaper. Clean off and dry.

Application:

- 1) Brush/Roller : The paint is ready to use after thorough stirring.
- 2) Compressed Air Spray: Thin 5-10% **CM 202 Thinner** by volume as necessary.

Recommended Paint System

Floor/ Wooden Surface

Sequence	Product Name	No. of Coats
Primer	-	-
Undercoat	-	-
Finish	CM Floor Dressing	1

Health, Safety and Environmental information:

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place.

Containers that are opened should be properly released and keep upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.