



CM GOLDEN PAINT

Product Code : CM GDP 1200/1220/1230/1240

Product Descriptions

CM Golden Paint is a premium quality, acrylic based paint. It gives excellent weathering properties, fungus and algae resistant. It will also provide a long lasting protection against fungus and algae growth if correct application adapted. It has a lifelike gold appearance and excellent aging resistance property.

Recommended Uses

Use for masonry coating, wood coating, concrete and general metal finishes. Commonly in used for hotels, dance halls, advertising plate, temples, decorating projects.

Product Characteristics

Composition:

Pigment	Metallic Gold Pigment
Binder	Acrylic resin
Solvent	Aromatic Hydrocarbon Solvent
Volume Solid	65%

Properties :

Colour Range	Super Gold ref: CM GDP 1200
	Copper Pink Gold ref: CM GDP 1220
	Rich Gold ref: CM GDP 1230
	Copper Gold ref: CM GDP 1240

Texture Gold Shine Finish

Shelf life/Storage Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. Up to 2 years storage life at 25'c to 30'c.

Standard Packing Size 30ml/ 250ml/ 1Litre /5 Litres

Typical Performance Data (approx.):

Coverage Approximately 8-10 m² per litre
*Actual coverage is dependent on substrate condition.
*These figures do not include wastage.

Recommended no. of coats 1-2 coats

Drying time (Application Temperature 25'c to 30'c)
Touch Dry: 30 Minutes
Hard Dry : ≥ 1 Hours

Recoating Interval ≥ 4 Hours

Directions for use

Preparation:

All surfaces must be clean, dry, free from grease and free from all defective or poorly adhering material. Abrade the surfaces with sandpaper if necessary. Oil and grease should be removed by solvent cleaning.

Application:

- 1) Brush/Roller : The paint is ready to use after thorough stirring. Thin 5% **CM 404 thinner** by volume if necessary.
- 2) Compressed Air Spray: Thin 10-15% **CM 404 Thinner** by volume as necessary.
- 3) Airless Spray: Ready to use. Thinning is not necessary.

Health, Safety and Environmental information:

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place.

Containers that are opened should be properly released and keep upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.