



CM TIMBER STAIN

(Exterior & Interior Varnish)

Product Code : TBS 1120/1130/1140/1150

Product Descriptions

CM Timber Stain is a durable pigmented varnish and solvent based on a special resin for protection and decoration purposes. It is flexible, water resistant, and durable and contains preservatives for protection of all timber surfaces against wood rot and mould growth. Its unique formulation will filter out UV rays minimalizing the traditional problems of cracking, flaking and peeling. It also lightens the surface slightly gloss.

Recommended Uses

Recommended use for all types of new or previously painted wooden surfaces. With its unique formulation, it is highly recommended use for the application on exterior and interior wooden surfaces, e.g. garden furniture, indoor furniture and arts & craft.

Product Characteristics

Composition:

Pigment	Transparent Pigment
Binder	Alkyd Modified Polyurethane
Solvent	
Volume Solid	40%

Properties :

Colour Range	Golden Pine Ref: TBS-1120 Teck Brown Ref: TBS-1130 Red Brown Ref: TBS-1140 Rosewood Ref: TBS-1150
Texture	Low Gloss
Shelf life/Storage	Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner.
Standard Packing Size	1 litre & 5 Litres *Other Sizes by special arrangement.

Typical Performance Data (approx.):

Coverage	Approximately 19m ² per litre *Actual coverage is dependent on substrate condition. *These figures do not include wastage.
Recommended no. of coats	1-2 coats
Drying time (Application Temperature 25'c to 30'c)	Touch Dry: 1-2 Hours Hard Dry : ≥ 4 Hours

Recoating Interval	≥ 4 hours
--------------------	-----------

Directions for use

Preparation:

All surfaces must be clean, dry, free from grease and free from all defective or poorly adhering material. Abrade the surfaces with sandpaper if necessary.

Wood

a) bare wood

1. Ensure surface is sound, clean, dry, smooth and free from wax before applying the first coat. Smoothen surface with sandpaper and then clean off and dry. Fill the wood grains with appropriate filler if necessary.

b) painted wood

1. Ensure surface is sound, clean, dry, smooth and free from wax before applying the first coat. Smoothen surface with sandpaper and then clean off and dry. Fill the wood grains with appropriate filler if necessary.
2. If the previous paint film is in sound condition and without wax, smoothen it with sandpaper. Clean off and dry.
3. For old paint which is in sound condition and without wax, smoothen it with sandpaper. Clean off and dry.

Application:

- 1) Brush/Roller : The paint is ready to use after thorough stirring. Thin 5% **CM 202 Thinner** by volume if necessary.
- 2) Compressed Air Spray: Dilute 10% **CM 202 Thinner** by volume if necessary.

Health, Safety and Environmental information:

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place.

Containers that are opened should be properly released and keep upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.

